


Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications
<p>*Precise cutting edges to improve drill performance with less effort</p> <p>*Countersunk head available for working purpose</p> <p>* Not Suitable for Marine or Coastal environments</p>	<ul style="list-style-type: none"> • Best choice for fastening in window or door frames purpose • Using in flat surface required • Using in pre-drilled holes for fitting • Hinges, gates & fences.

Finish	Material	Head
Passivated	Stainless Steel (G410)	Countersunk Square Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Screw Diameter	Head Diameter	Drive Square	Drilling Capacity of steel
	#	(mm)	L (mm)		(mm)		D (Max)	A (Max)	#
Coarse Thread									
A1SDCSQ10-1625	10	4.8	25	16	Full	4.8	9.19	2	1.0-4.0
A1SDCSQ10-1630	10	4.8	30	16	Full	4.8	9.19	2	1.0-4.0
A1SDCSQ10-1640	10	4.8	40	16	Full	4.8	9.19	2	1.0-4.0
Fine Thread									
A1SDCSQ10-2430	10	4.8	30	24	Full	4.8	9.19	2	2.0-4.0
A1SDCSQ10-2440	10	4.8	40	24	Full	4.8	9.19	2	2.0-4.0
A1SDCSQ10-2450	10	4.8	50	24	Full	4.8	9.19	2	2.0-4.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

