




## **Security Self Drilling Screws**

Stainless Steel(G410)

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Pan head design on purpose using Security purpose using	Skin sheet to steel Residential frame construction For light duty purpose	Under 3000RPM drill speed	#8 - 1.0-2.0mm of steel #10 - 1.0-3.0mm of steel





Finish	Material	Head
Passivated	Stainless Steel (G410)	Pan Torx Drive with pin

Product Code SKU	Gauge		Length	Threads per inch	Thread Length	Diameter D (Max)	Head Diameter (Max)	Head Height	Torx Drive with pin	Drilling Point Length
	#	(mm)	L (mm)	(TPI)	TL (mm)	D (mm)	A (mm)	H (mm)	#	C (mm)
A1SDPTP08-1812	8	4.2	12	18	Full	4.04 - 4.21	7.8-8.1	2.7-2.9	T20	4.0-6.0
A1SDPTP08-1820	8	4.2	20	18	Full	4.04 – 4.21	7.8-8.1	2.7-2.9	T20	4.0-6.0
A1SDPTP08-1825	8	4.2	25	18	Full	4.04 - 4.21	7.8-8.1	2.7-2.9	T20	4.0-6.0
A1SDPTP08-1832	8	4.2	32	18	Full	4.04 – 4.21	7.8-8.1	2.7-2.9	T20	4.0-6.0
A1SDPTP10-1612	10	4.8	12	16	Full	5.46 - 5.74	9.1-9.4	3.1-3.3	T25	5.0-7.0
A1SDPTP10-1620	10	4.8	20	16	Full	5.46 - 5.74	9.1-9.4	3.1-3.3	T25	5.0-7.0
A1SDPTP10-1625	10	4.8	25	16	Full	5.46 - 5.74	9.1-9.4	3.1-3.3	T25	5.0-7.0
A1SDPTP10-1632	10	4.8	32	16	Full	5.46 - 5.74	9.1-9.4	3.1-3.3	T25	5.0-7.0
A1SDPTP10-1640	10	4.8	40	16	Full	5.46 - 5.74	9.1-9.4	3.1-3.3	T25	5.0-7.0

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

