




Self Drilling Screws – Bi-Matel

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Pan head design on purpose using Non-walking point provides fast material engagement	<ul style="list-style-type: none"> • Skin steel to steel • Residential steel frame construction • For Light duty purpose 	2300-2500 RPM max drill speed	1.0-3.0mm of steel

Material	Finish	Head
Bi-Matel Body: Stainless Steel (A4 316) Point: Carbon Steel (C1022)	Ruspert [®] Plated	Pan Square Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Drive Square	Drilling Point Length
	#	(mm)	L (mm)		(mm)			#	C (mm)
Coarse Thread									
A4SDPSQ08-1816	8	4.2	16	18	Full	4.04-4.22	7.77-8.18	2	4.0-5.0
A4SDPSQ08-1820	8	4.2	20	18	Full	4.04-4.22	7.77-8.18	2	4.0-5.0
A4SDPSQ08-1825	8	4.2	25	18	Full	4.04-4.22	7.77-8.18	2	4.0-5.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

