





### Self Drilling Screws – Bi-Matel

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Wafer head design on purpose using Non-walking point provides fast material engagement	<ul style="list-style-type: none"> <li>Roof and skin sheet to steel</li> <li>Residential steel frame construction</li> <li>For Light duty purpose</li> </ul>	2300-2500 RPM max drill speed	1.0-3.0mm of steel

Material	Finish	Head
Bi-Matel Body: Stainless Steel (A4 316) Point: Carbon Steel (C1022)	Ruspert <sup>®</sup> Plated	Wafer Phillips Recess

Product Code SKU	Gauge		Length L (mm)	Threads Per inch (TPI)	Thread Length (mm)	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Drive Phillips #	Drilling Point Length C (mm)
	#	(mm)							
<b>Coarse Thread</b>									
A4SDW10-1616	10	4.8	16	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
A4SDW10-1622	10	4.8	22	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
A4SDW10-1630	10	4.8	30	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7

1300 532 803  
 sales@tower-tr.com.au  
 www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

