



Self Drilling Screws - Bi-Matel

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Wafer head design on purpose using Non-walking point provides fast material engagement	- Roof and skin sheet to steel - Residential steel frame construction - For Light duty purpose	2300-2500 RPM max drill speed	1.0-4.0mm of steel

Material	Finish	Head
Bi-Matel Body: Stainless Steel (A4 316) Point: Carbon Steel (C1022)	Ruspert [®] Plated	Wafer Torx Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Screw Diameter	Head Diameter	Drive Torx	Drilling Point Length
	#	(mm)	L (mm)		(mm)	D (mm)	A (mm)	#	C (mm)
A4SDWTX12-1425	12	5.5	25	14	Full	5.3-5.46	10.9-11.4	T25	7.5-8.5

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

