




Self Drilling Screws – Stainless (YUS 550)

*Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.

* YUS 550 Stainless Self Drilling performance superior to Bi-Metal 304, replacement for A2 304 Self-Drilling Bi-Metal Screws.



Features	Applications
<ul style="list-style-type: none"> High-Strength heat-treated martensite stainless steel suitable for direct sheet metal application. High Hardness (Min. 600HV) and strength equivalent to G410 Stainless Steel. Superior corrosion resistance equivalent to A2 304 Stainless Steel. 	<ul style="list-style-type: none"> Best choice for fastening in window or door frames purpose Using in flat surface required Using in pro-drilled holes for fitting Hinges, gates & fences.

Finish	Material	Head
Passivated	Stainless Steel (YUS 550)	Countersunk Square Recess

Product Code SKU	Gauge		Length L (mm)	Threads Per inch (TPI)	Thread Length (mm)	Screw Diameter D (Max)	Head Diameter A (Max)	Drive Square #	Drilling Capacity of steel (mm)
	#	(mm)							
Fine Thread									
A5SDCSQ10-2430	10	4.8	30	24	Full	4.82	9.19	2	1.0-3.0
A5SDCSQ10-2440	10	4.8	40	24	Full	4.82	9.19	2	1.0-3.0
A5SDCSQ10-2450	10	4.8	50	24	Full	4.82	9.19	2	1.0-3.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

