




Stainless Steel (YUS 550) Self Drilling Screws

S500 (Extended No.5 Point) Screws

Stainless (YUS 550) Self Drilling performance superior to Bi-Metal 304, replacement for A2 304 Self-Drilling Bi-Metal Screws



Features	Applications	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> • High-Strength heat-treated martensite stainless steel suitable for direct sheet metal application. • High Hardness (Min. 600HV) and strength equivalent to Stainless Steel (G410). • Superior corrosion resistance equivalent to Stainless Steel (A2 304). 	<ul style="list-style-type: none"> • For heavy duty purpose • Metal deck to structural steel or bar joist • Clip to structural or bar joist • longer length fasteners for sheet applications 	1800 RPM max drill speed	6-12mm steel

Finish	Material	Head
Passivated	Stainless Steel (YUS 550)	Hex Flange Washer

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length (mm)	Diameter (Max) (mm)	Head Diameter (Max) (mm)	Head Height (mm)	Hex. Socket (inch)	Cutting Length (mm)
	#	(mm)								
A5SDHE12-2445	12	5.5	45	24	Full	5.28-5.46	13.97-14.70	5.08-5.90	5/16"	15.0-16.0
A5SDHE12-2465	12	5.5	65	24	Full	5.28-5.46	13.97-14.70	5.08-5.90	5/16"	15.0-16.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

