


## Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.

YUS 550 Stainless Self Drilling performance superior to Bi-Metal 304, replacement for A2 304 Self-Drilling Bi-Metal Screws.



Features	Applications	Installation Speed	Drill Capacity
Wafer head design on purpose using Non-walking point provides fast material engagement	<ul style="list-style-type: none"> <li>Roof and skin sheet to steel</li> <li>Residential steel frame construction</li> <li>For Light duty purpose</li> </ul>	2300-2500 RPM max drill speed	1.0-4.0mm of steel

Material	Finish	Head
Stainless Steel (YUS 550)	Passivated	Wafer Torx Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Screw Diameter	Head Diameter	Drive Torx	Drilling Point Length
	#	(mm)	L (mm)		(mm)		A (mm)		C (mm)
A5SDWTX12-1425	12	5.5	25	14	Full	5.30-5.46	10.99-11.44	T25	7.5-8.5

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

