




Bulb-tite (Tri-Firm) Blind Rivets with NEO (Waterproof)

A bulb tite blind rivet provides a 'Y' shaped split tail formation, providing a large blind side bearing area. This will also provide a relatively high resistance to pull out loads.









Ad	van	tao	e:	
-	A. C.	1	٠.	

- * Resists pull-out and cracking the work piece
- * Extra large secondary head provides more bearing surface
- * With the wide spreading tail, this rivet has a greater tolerance of oversized holes and offer a wide grip range
- * Waterproof with EPDM Neo

Applications

- Soft Material such as wood
- Insulation
- Plastic
- Plaster boards

	Material	Finish	Head
Body: Mandrel: Washer:	Aluminum 5056 Aluminum Alloy EPDM NEO	Natural Polish Natural Polish	Dome (Trust)

Product Code SKU	Size		Body Length	Head Height	Head Dia. (Max)	Mandrel (Ref)	Hole Size	Grip Range	Tensile	Shear
	D (mm)	Inch	L (±1)mm	E (mm)	H (mm)	P (mm)	(mm)	(mm)	N	N
AADBTN6-3	5.2	13/64"	17.5	3.4	11.6	27	5.35.5	1.3-4.8	1800	2700
AADBTN6-4	5.2	13/64"	19.5	3.4	11.6	27	5.35.5	1.6-6.4	1800	2700
AADBTN6-6	5.2	13/64"	22.6	3.4	11.6	27	5.35.5	4.7-9.5	1800	2700
AADBTN6-8	5.2	13/64"	25.8	3.4	11.6	27	5.35.5	7.9-12.7	1800	2700
AADBTN6-10	5.2	13/64"	29.0	3.4	11.6	27	5.35.5	11.1-15.9	1800	2700
AADBTN6-12	5.2	13/64"	32.0	3.4	11.6	27	5.35.5	14.3-19.1	1800	2700
AADBTN8-4	6.4	1/4"	20.5	4.0	14.7	27	6.4-6.6	1.6-6.4	2500	3780
AADBTN8-6	6.4	1/4"	23.7	4.0	14.7	27	6.4-6.6	3.2-9.5	2500	3780
AADBTN8-8	6.4	1/4"	26.8	4.0	14.7	27	6.4-6.6	6.4-12.7	2500	3780
AADBTN8-10	6.4	1/4"	30.0	4.0	14.7	27	6.4-6.6	9.5-15.9	2500	3780

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

