



Chipboard Screws

AS3566 Class3

Chipboard screws have coarse threads and fine shanks, designed for use in chipboards and soft woods.



Features	Applications	Installation Speed	Drill Capacity
- Coarse threads and fine shanks, - Csk.rib head available for working purpose	- Chipboard - Soft timbers	2300 -2500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert [®] Plated	Carbon Steel	Countersunk Rib. Square Drive

Product Code SKU	Gauge		Length L (mm)	Threads per inch (TPI)	Thread Length TL (mm)	Diameter B (mm)	Head Diameter A (mm)	Pitch P (mm)	Square Drive #
	#	(mm)							
CBSQG0816	8	4.2	16	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQG0820	8	4.2	20	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQG0825	8	4.2	25	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQG0828	8	4.2	28	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQG0832	8	4.2	32	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQG0835	8	4.2	35	10	25	4.2-4.5	7.42-8.43	2.54	2
CBSQG0838	8	4.2	38	10	28	4.2-4.5	7.42-8.43	2.54	2
CBSQG0841	8	4.2	41	10	28	4.2-4.5	7.42-8.43	2.54	2
CBSQG0845	8	4.2	45	10	32	4.2-4.5	7.42-8.43	2.54	2
CBSQG0850	8	4.2	50	10	35	4.2-4.5	7.42-8.43	2.54	2
CBSQG1050	10	4.8	50	10	35	4.7-5.0	8.64-9.77	2.54	2
CBSQG1065	10	4.8	65	10	35	4.7-5.0	8.64-9.77	2.54	2
CBSQG1075	10	4.8	75	10	50	4.7-5.0	8.64-9.77	2.54	2
CBSQG10100	10	4.8	100	10	50	4.7-5.0	8.64-9.77	2.54	2
CBSQG10125	10	4.8	125	10	65	4.7-5.0	8.64-9.77	2.54	2
CBSQG10150	10	4.8	150	10	65	4.7-5.0	8.64-9.77	2.54	2

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

