



Chipboard Screws

Zinc Plated

Chipboard screws have coarse threads and fine shanks, designed for use in chipboards and soft woods.



Features	Applications	Installation Speed	Drill Capacity
- Coarse threads and fine shanks, - Csk.rib head available for working purpose	- Chipboard - Soft timbers	2300 -2500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Trivalent Zinc Plated	Carbon Steel	Countersunk Rib. Square Drive

Product Code SKU	Gauge		Length L (mm)	Threads per inch (TPI)	Thread Length TL (mm)	Diameter B (mm)	Head Diameter A (mm)	Pitch P (mm)	Square Drive #
	#	(mm)							
CBSQT0820	8	4.2	20	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQT0825	8	4.2	25	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQT0828	8	4.2	28	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQT0832	8	4.2	32	10	Full	4.2-4.5	7.42-8.43	2.54	2
CBSQT0835	8	4.2	35	10	25	4.2-4.5	7.42-8.43	2.54	2
CBSQT0838	8	4.2	38	10	28	4.2-4.5	7.42-8.43	2.54	2
CBSQT0841	8	4.2	41	10	28	4.2-4.5	7.42-8.43	2.54	2
CBSQT0845	8	4.2	45	10	32	4.2-4.5	7.42-8.43	2.54	2
CBSQT0850	8	4.2	50	10	35	4.2-4.5	7.42-8.43	2.54	2
CBSQT1065	10	4.8	65	10	35	4.7-5.0	8.64-9.77	2.54	2
CBSQT1075	10	4.8	75	10	50	4.7-5.0	8.64-9.77	2.54	2
CBSQT10100	10	4.8	100	10	50	4.7-5.0	8.64-9.77	2.54	2

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

