




Drywall Screws AS3566 Class3

Drywall screws are traditionally used to attach drywall to metal and wood, but also have many other external applications.

Long size screws using to joint of composite panel or wall panel

Features	Applications	Installation Speed	Drill Capacity
Bugle head Needle point	For fixing to	2300 -2500 RPM max drill speed	<1.0mm thin steel



Finish	Material	Head
Ruspert [®] Plated	Carbon Steel	Bugle Phillips Drive Square Drive

Product Code SKU	Gauge		Length	Threads per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive
	#	(mm)	L (mm)		TL (mm)	B (mm)	A (mm)	#
DWBG06-1825	6	3.5	25	18	Full	3.4-3.6	8.0-8.5	Phillips #2
DWBSQG08-1565	8	4.2	65	15	Full	4.11-4.26	8.0-8.5	Square #2
DWBSQG08-1575	8	4.2	75	15	65	4.11-4.26	8.0-8.5	Square #2
DWBSQG10-12100	10	4.8	100	12	75	4.7-4.95	8.0-8.5	Square #2
DWBSQG10-12130 DWBSQG10-12150	10 10	4.8 4.8	130 150	12 12	75 100	4.7-4.95 4.7-4.95	8.0-8.5 8.0-8.5	Square #2 Square #2

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

