


Open Blind Rivet

Blind Rivets are now capable in every industrial field to replace Welding, Tapping Screws or Bolts & Nuts and to fasten materials speedy and securely from one side of the work by using an exclusive fastening tool.



Advantage:	Applications
* Strong but lower cost fastener * Available in variety of materials and ideal for wide range of applications * Painted colour finished available to match surrounding	• Office furniture • Automotive • Building • Construction • Leather production

	Material	Finish	Head
Body: Mandrel:	Stainless (A2 304) Steel	Natural Polish Zinc Plated	Dome (Truss)

Product Code SKU	Size		Body Length	Head Height	Head Dia. (Max)	Mandrel (Ref)	Hole Size	Grip Range	Tensile	Shear
	D (mm)	Inch								
KSD4-2	3.2	1/8"	6	1.3	6.7	27	3.3-3.4	1.0-3.5	2500	1900
KSD4-3	3.2	1/8"	8	1.3	6.7	27	3.3-3.4	3.5-5.0	2500	1900
KSD4-4	3.2	1/8"	10	1.3	6.7	27	3.3-3.4	5.0-7.0	2500	1900
KSD4-6	3.2	1/8"	14	1.3	6.7	27	3.3-3.4	7.0-11.0	2500	1900
KSD5-2	4.0	5/32"	8	1.7	8.4	27	4.1-4.2	3.0-5.0	3500	2700
KSD5-3	4.0	5/32"	10	1.7	8.4	27	4.1-4.2	4.0-6.5	3500	2700
KSD5-4	4.0	5/32"	12	1.7	8.4	27	4.1-4.2	6.0-8.5	3500	2700
KSD5-5	4.0	5/32"	14	1.7	8.4	27	4.1-4.2	7.0-10.5	3500	2700
KSD5-6	4.0	5/32"	16	1.7	8.4	27	4.1-4.2	8.0-12.5	3500	2700
KSD6-2	4.8	3/16"	8	2.0	10.1	27	4.9-5.0	1.0-4.0	5000	4000
KSD6-3	4.8	3/16"	10	2.0	10.1	27	4.9-5.0	4.0-6.0	5000	4000
KSD6-4	4.8	3/16"	12	2.0	10.1	27	4.9-5.0	6.0-8.0	5000	4000
KSD6-5	4.8	3/16"	14	2.0	10.1	27	4.9-5.0	8.0-10.0	5000	4000
KSD6-6	4.8	3/16"	16	2.0	10.1	27	4.9-5.0	9.0-12.0	5000	4000
KSD6-8	4.8	3/16"	18	2.0	10.1	27	4.9-5.0	10.0-14.0	5000	4000
KSD6-10	4.8	3/16"	20	2.0	10.1	27	4.9-5.0	12.0-16.0	5000	4000
KSD6-12	4.8	3/16"	25	2.0	10.1	27	4.9-5.0	16.0-21.0	5000	4000

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

