




## Self Tapping Screws - Undercut

(Hinge Screws)

Self-Tapping screws are designed to create a thread while being suitable for wood, sheet metal and plastics.



1			
ı	THEFT		D
1	Brown A	4444	





Features	Applications	
Undercut Countersunk Head fasteners are designed to be countersunk flush or slightly sunken into the surface of the material	<ul><li>Hinge</li><li>Sheet Metal</li><li>Timber</li><li>Some Plastics</li></ul>	

Finish	Material	Head
Polished	Stainless Steel (A2 304)	Countersunk - UnderCut Phillips Recess

Product Code	Ga	uge	Length	Threads per	Thread Length	Diameter	Head Diameter	Phillips Drive
SKU	#	(mm)	L (inch)	inch (TPI)	(mm)	D (mm)	A (mm)	(#)
KSTC0810UC	8	4.2	3/8"	18	Full	4.04 - 4.21	7.42 - 8.43	2
KSTC0812UC	8	4.2	1/2"	18	Full	4.04 - 4.21	7.42 - 8.43	2
KSTC0820UC	8	4.2	3/4"	18	Full	4.04 - 4.21	7.42 - 8.43	2
KSTC0825UC	8	4.2	1"	18	Full	4.04 - 4.21	7.42 - 8.43	2
KSTC1010UC	10	4.8	3/8"	16	Full	4.62 - 4.80	8.64 - 9.77	2
KSTC1012UC	10	4.8	1/2"	16	Full	4.62 - 4.80	8.64 - 9.77	2
KSTC1016UC	10	4.8	5/8"	16	Full	4.62 - 4.80	8.64 - 9.77	2
KSTC1020UC	10	4.8	3/4"	16	Full	4.62 - 4.80	8.64 - 9.77	2
KSTC1025UC	10	4.8	1"	16	Full	4.62 - 4.80	8.64 - 9.77	2
KSTC1225UC	12	5.5	1"	14	Full	5.31 - 5.46	9.88 - 11.12	3
KSTC1230UC	12	5.5	1-1/4"	14	Full	5.31 - 5.46	9.88 - 11.12	3

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

