




**NEO Washer (EPDM)**



| Features  | Applications |
|---|--------------|
| <p>* Sealing washers are designed to prevent fluids from entering a screw's entry point by sealing the screw and the contact point.</p> <p>* Macromolecule material, the EPDM NEO contains excellent characters of aging, ultraviolet rays resistance and endure to ozone, high and low temperature (-50°C - 150°C)</p> |              |

| Material  |
|---|
| EPDM Rubber - (Ethylene Propylene Diane Monomer rubber) |

| Product Code<br>SKU | Outside Diameter MAX | Inside Diameter | Thickness |
|---------------------|----------------------|-----------------|-----------|
|                     | OD (mm)              | ID (mm)         | Thk (mm)  |
| NEO-08G             | 8.5                  | 3.7             | 2.2       |
| NEO-10G             | 8.8                  | 4.3-5.1         | 2.6       |
| NEO-12G             | 10.7                 | 4.6-6.0         | 2.8       |
| NEO-14G             | 11.4                 | 5.4-6.7         | 2.8       |

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
 ©TOWER Fastening System. All rights reserved. Version: 2309

