




### Self Drilling Screws - Reduced Point

#### For Metal and Timber

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> <li>• Double thread for the purpose using exterior roofing environment.</li> <li>• High thread under the head prevents panel strip out.</li> <li>• Reduced Point design for fastening roof panel to thin steel battens, or timber, or steel purling (&lt;1.9mm)</li> <li>• Coarse Thread</li> </ul>	2300-3000 RPM max drill speed	0.5-1.9mm of steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Hexagon Flange Washer With EPDM NEO

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Socket	Drilling Point Length
	#	(mm)	L (mm)						
RSDHCDN14-1150	14	6.3	50	11	Double Thread	5.31-5.46	14.0-14.7	3/8"	6.7 - 8.0

1300 532 803  
sales@tower-tr.com.au  
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
©TOWER Fastening System. All rights reserved. Version: 2309

