




Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Applications	_	Installation Speed	Drill Capacity	
* Stitch timber to metal * Using in flat surface Requires * Fixing Plasterboard to Metal		2300-2500 RPM max drill speed	1-2.0mm of steel	





Finish	Material	Head
Ruspert [®] Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Bugle Square Recess

Product Code SKU	Gauge		auge Length	Threads Per inch	Thread Length	Diameter (Max)	Head Diameter (Max)	Drive Square	Drilling Point Length
	#	(mm)	L (mm)	(TPI)	TL(mm)	D (mm)	A (mm)	#	C (mm)
SDBSQG06-2025	6	3.5	25	20	Full	3.42-3.53	8.0-8.5	1	3.0-4.5
SDBSQG06-2032	6	3.5	32	20	Full	3.42-3.53	8.0-8.5	1	3.0-4.5

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

©TOWER Fastening System. All rights reserved. Version: 2309

