




Self Drilling Screws – (S500 Screws)

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
* Engineered for fast drilling and smooth tapping with less effort * Countersunk head available for working purpose	<ul style="list-style-type: none"> For heavy duty purpose Metal deck to structural steel or bar joist Clip to structural or bar joist Longer length fasteners for sheet applications Using in flat surface required 	2300-2500 RPM max drill speed	5.0-12.0mm of steel

Finish	Material	Head
Ruspert [®] Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Countersunk Square Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length (mm)	Diameter D (mm)	Head Diameter A (mm)	Drive Square #	Drilling Point Length C (mm)
	#	(mm)	L (mm)						
SDCSQCE12-2438	12	5.5	38	24	Full	5.27-5.46	9.88-11.12	3	15.0-15.5
SDCSQCE12-2450	12	5.5	50	24	Full	5.27-5.46	9.88-11.12	3	15.0-15.5
SDCSQCE12-2465	12	5.5	65	24	Full	5.27-5.46	9.88-11.12	3	15.0-15.5
SDCSQCE12-2485	12	5.5	85	24	Full	5.27-5.46	9.88-11.12	3	15.0-15.5
SDCSQCE12-24100	12	5.5	100	24	Full	5.27-5.46	9.88-11.12	3	15.0-15.5

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

