



## Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Precise cutting edges to improve drill performance with less effort Countersunk head available for working purpose	<ul style="list-style-type: none"> <li>Best choice for fastening in window or door frames purpose</li> <li>Using in flat surface required</li> </ul>	2300-2500 RPM max drill speed	>3.0mm of steel

Finish	Material	Head
Zinc Yellow Plated	Carbon Steel (C1022)	Countersunk Phillips Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Phillips	Drilling Point Length
	#	(mm)	L (mm)		(mm)		A (mm)	#	C (mm)
SDCYE06-2050	6	3.5	50	20	23.0	3.34 – 3.53	6.20 – 7.08	2	4.50 – 5.50
SDCYE06-2065	6	3.5	65	20	30.0	3.34 – 3.53	6.20 – 7.08	2	4.50 – 5.50

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
 ©TOWER Fastening System. All rights reserved. Version: 2309

