



Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Flat Top head design on purpose using	<ul style="list-style-type: none"> Residential steel frame construction with plasterboard For Light duty purpose 	2300-2500 RPM max drill speed	1.0-3.0mm of steel

Finish	Material	Head
* Ruspert [®] Plated Complies with AS3566 Class 4 * Zinc Yellow Plated	Carbon Steel (C1022)	Flat Top Phillips Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Phillips	Drilling Point Length
	#	(mm)	L (mm)		(mm)	D (mm)	A (mm)	#	C (mm)
Ruspert® Plated									
SDFTC10-1616	10	4.8	16	16	Full	4.62-4.82	7.9-8.1	2	5.7-6.7
SDFTC10-1622	10	4.8	22	16	Full	4.62-4.82	7.9-8.1	2	5.7-6.7
SDFTC10-1630	10	4.8	30	16	Full	4.62-4.82	7.9-8.1	2	5.7-6.7
Zinc Yellow									
SDFTY10-1616	10	4.8	16	16	Full	4.62-4.82	7.9-8.1	2	5.7-6.7

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

