


### Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> <li>• Double thread for the purpose using exterior roofing environment.</li> <li>• High thread under the head prevents panel strip out.</li> </ul>	<ul style="list-style-type: none"> <li>*Roof and wall panel over rigid insulation to steel framing</li> <li>* Roof panel over space block and insulation to eaves purling.</li> </ul>	2300-3000 RPM max drill speed	2.0-4.0mm of steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated complies with AS3566 Class 4 complies with AS3566 Class 3	Carbon Steel (C1022)	Hexagon Flange Washer With EPDM NEO

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Socket	Drilling Point Length
	#	(mm)	L (mm)						
							A (mm)		
Class3									
SDHGDN12-1448	12	5.5	48	14	Double Thread	5.31 – 5.46	14.0-14.2	5/16	6.7 – 8.0
Class4									
SDHCDN12-1435	12	5.5	35	14	Double Thread	5.31 – 5.46	14.0-14.2	5/16	6.7 – 8.0
SDHCDN12-1445	12	5.5	45	14	Double Thread	5.31 – 5.46	14.0-14.2	5/16	6.7 – 8.0
SDHCDN12-1455	12	5.5	55	14	Double Thread	5.31 – 5.46	14.0-14.2	5/16	6.7 – 8.0
SDHCDN12-1468	12	5.5	68	14	Double Thread	5.31 – 5.46	14.0-14.2	5/16	6.7 – 8.0

1300 532 803  
sales@tower-tr.com.au  
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
©TOWER Fastening System. All rights reserved. Version: 2309

