


### Self Drilling Screws

#### S500 (Extended No.5 Point) Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Engineered for fast drilling and smooth tapping with less effort.	<ul style="list-style-type: none"> <li>• For heavy duty purpose</li> <li>• Metal deck to structural steel or bar joist</li> <li>• Clip to structural or bar joist</li> <li>• longer length fasteners for sheet applications</li> </ul>	2300-3000 RPM max drill speed	6-12mm steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Hex Flange Washer

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length (mm)	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Head Height H (mm)	Hex. Socket (inch)	Cutting Length (mm)
	#	(mm)								
SDHCE14-2438	14	6.3	38	24	Full	5.31-5.46	14.0-14.2	6.35-7.0	3/8"	15.0-16.0

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
 ©TOWER Fastening System. All rights reserved. Version: 2309

