




Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> • Unique point to thread design extrudes the metal preventing strip out • Non-walking point provides fast material engagement • Point to thread design maximizes pullout performance and minimizes back out 	<ul style="list-style-type: none"> * For light duty purpose * For medium duty purpose * Roof Deck to steel framing * Accessories to steel framing 	2300-2500 RPM max drill speed	#10 – 1.0-3.0mm of steel #12 – 2.0-4.0mm of steel #14 – 2.0-5.0mm of steel

Finish	Material	Head
Ruspert [®] Plated complies with AS3566 Class 3	Carbon Steel (C1022)	Hexagon Flange Washer

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Socket	Drilling Point Length
	#	(mm)	L (mm)		(mm)	D (mm)	A (mm)		C (mm)
Coarse Thread									
SDHG10-1616	10	4.8	16	16	Full	4.62-4.80	10.85-11.45	5/16	5.7-6.7
SDHG12-1420	12	5.5	20	14	Full	5.31-5.46	14.0-14.2	5/16	7.5-8.5
SDHG14-1022	14	6.3	22	10	Full	6.11-6.32	14.0-14.7	1/4	7.9-9.0
Fine Thread									
SDHG10-2416	10	4.8	16	24	Full	4.66-4.83	10.85-11.45	5/16	5.7-6.7
SDHG14-2022	14	6.3	22	20	Full	6.11-6.32	14.0-14.7	1/4	7.9-9.0
SDHG14-20150	14	6.3	150	20	100	6.11-6.32	14.0-14.7	1/4	7.9-9.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

