



### Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> <li>* Button Head design on purpose using</li> <li>* Non-walking point provides fast material engagement</li> </ul>	<ul style="list-style-type: none"> <li>* Residential steel frame construction</li> <li>* For using in object polycarbonate sheet, shadow cove</li> </ul>	2300-2500 RPM max drill speed	1-3.0mm of steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Button Phillips Recess

Product Code SKU	Gauge		Length L (mm)	Threads Per inch (TPI)	Thread Length TL(mm)	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Drive Phillips #	Drilling Point Length C (mm)
	#	(mm)							
SDLC08-1812	8	4.2	12	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLC08-1816	8	4.2	16	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLC08-1820	8	4.2	20	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLC08-1825	8	4.2	25	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLC08-1832	8	4.2	32	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.  
 ©TOWER Fastening System. All rights reserved. Version: 2309

