




Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
* Button Head design on purpose using * Non-walking point provides fast material engagement	* Residential steel frame construction * For using in object polycarbonate sheet, shadow cove	2300-2500 RPM max drill speed	1-3.0mm of steel





Finish	Material	Head
Zinc Yellow Plated Zinc Plate	Carbon Steel (C1022)	Button Phillips Recess Square Recess

Product Code SKU	C	Sauge	Length	Threads Per inch	Thread Length	Diameter (Max)	Head Diameter (Max)	Drive Phillips	Drilling Point Length
	#	(mm)	L (mm)	(TPI)	TL(mm)	D (mm)	A (mm)	#	C (mm)
Zinc Plated									
SDLZ08-1809	8	4.2	9	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
Zinc Yellow									
SDLY08-1812	8	4.2	12	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLY08-1816	8	4.2	16	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLY08-1820	8	4.2	20	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLY08-1825	8	4.2	25	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLY08-1832	8	4.2	32	18	Full	4.09-4.21	10.8-11.2	2	4.7-5.7
SDLY10-1616	8	4.2	16	16	Full	4.09-4.21	10.8-11.2	2	5.7-6.7
Zinc Plated								Square Drive	
SDLZSQ10-1616	8	4.2	16	16	Full	4.09-4.21	10.8-11.2	2	5.7-6.7

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

©TOWER Fastening System. All rights reserved. Version: 2309

