



Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Material	Finish	Head
Carbon Steel (C1022)	Zinc Plated	Pan Phillips Recess

Features	Applications	Installation Speed	Drill Capacity
* Pan head designed for purpose using * Non-walking point provides fast material engagement	<ul style="list-style-type: none"> Skin steel to steel Residential steel frame construction For Light duty purpose 	2300-2500 RPM max drill speed	#6 -0.5-2.0mm of steel #8 - 1.0-3.0mm of steel

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Screw Diameter	Head Diameter	Head Height	Drive Phillips	Drilling Point Length
	#	(mm)	L (mm)		(mm)					
SDPZ06-2010	6	3.5	10	20	Full	3.42-3.53	6.50-6.85	2.21-2.46	2	3.0-4.5
SDPZ06-2012	6	3.5	12	20	Full	3.42-3.53	6.50-6.85	2.21-2.46	2	3.0-4.5
SDPZ06-2016	6	3.5	16	20	Full	3.42-3.53	6.50-6.85	2.21-2.46	2	3.0-4.5
SDPZ06-2020	6	3.5	20	20	Full	3.42-3.53	6.50-6.85	2.21-2.46	2	3.0-4.5
SDPZ08-1812	8	4.2	12	18	Full	4.09-4.21	7.77-8.17	2.67-2.92	2	4.7-5.7
SDPZ08-1816	8	4.2	16	18	Full	4.09-4.21	7.77-8.17	2.67-2.92	2	4.7-5.7
SDPZ08-1822	8	4.2	22	18	Full	4.09-4.21	7.77-8.17	2.67-2.92	2	4.7-5.7
SDPZ08-1825	8	4.2	25	18	Full	4.09-4.21	7.77-8.17	2.67-2.92	2	4.7-5.7

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

