




Self Drilling Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
* Precise cutting edges to improve drill performance with less effort * Countersunk head available for working purpose	<ul style="list-style-type: none"> Using in flat surface required 	2300-2500 RPM max drill speed	1.0-3.0 of steel

Finish	Material	Head
Rusper [®] Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Csk. Rib Square Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter	Head Diameter	Drive Square	Drilling Point Length
	#	(mm)	L (mm)		(mm)		D (mm)		A (mm)
SDSQC10-16100	10	4.8	100	16	Full	4.62-4.8	8.64-9.77	2	5.7-6.7
SDSQC10-16125	10	4.8	125	16	100	4.62-4.8	8.64-9.77	2	5.7-6.7

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.
 ©TOWER Fastening System. All rights reserved. Version: 2309

