




### Self Drilling Screws - AS3566 Class3

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Wafer head design on purpose using Non-walking point provides fast material engagement	<ul style="list-style-type: none"> <li>Roof and skin sheet to steel</li> <li>Residential steel frame construction</li> <li>For Light duty purpose</li> </ul>	2300-2500 RPM max drill speed	#8 - 1.0-2.0mm #10 - 1.0-3.0mm

Finish	Material	Head
Ruspert <sup>®</sup> Plated complies with AS3566 Class 3	Carbon Steel (C1022)	Wafer Phillips Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter (Max)	Head Diameter (Max)	Drive Phillips #	Drilling Point Length
	#	(mm)	L (mm)		(mm)	D (mm)	A (mm)		C (mm)
SDWG08-1812	8	4.2	12	18	Full	4.09 – 4.21	7.7-8.2	2	4.7-5.7
SDWG10-1616	10	4.8	16	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWG10-1622	10	4.8	22	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWG10-1630	10	4.8	30	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

