




Self Drilling Screws—S500 Screws

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
<ul style="list-style-type: none"> * Wafer head design on purpose using * Non-walking point provides fast material engagement * Engineered for fast drilling and smooth tapping with less effort 	<ul style="list-style-type: none"> • Metal deck to structural steel or bar joist • Clip to structural or bar joist • For heavy duty purpose • Longer length fasteners for sheet applications 	2200 RPM max drill speed	5.0-12.0mm of steel

Finish	Material	Head
Ruspert [®] Plated complies with AS3566 Class 4	Carbon Steel (C1022)	Wafer Phillips Recess Square Recess

Product Code SKU	Gauge		Length L (mm)	Threads Per inch (TPI)	Thread Length (mm)	Diameter (Max) D (mm)	Head Diameter A (mm)	Drive Phillips #	Drilling Point Length C (mm)
	#	(mm)							
SDWCE12-2432	12	5.5	32	24	Full	5.27-5.46	10.40-10.80	3	15.0-15.5
SDWCE12-2450	12	5.5	50	24	Full	5.27-5.46	10.40-10.80	3	15.0-15.5
Square Drive									
SDWSQCE12-2432	12	5.5	32	24	Full	5.27-5.46	10.40-10.80	3	15.0-15.5
SDWSQCE12-2438	12	5.5	38	24	Full	5.27-5.46	10.40-10.80	3	15.0-15.5
SDWSQCE12-2450	12	5.5	50	24	Full	5.27-5.46	10.40-10.80	3	15.0-15.5

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

