


Self Drilling Screws - AS3566 Class4

Self-Drilling screws are designed to have a drill-shaped point for use with metal, without having to drill a pilot hole beforehand.



Features	Applications	Installation Speed	Drill Capacity
Wafer head design on purpose using Non-walking point provides fast material engagement	<ul style="list-style-type: none"> Roof and skin sheet to steel Residential steel frame construction For Light duty purpose 	2300-2500 RPM max drill speed	1.0-3.0mm of steel

Finish	Material	Head
Zinc Yellow Plated	Carbon Steel (C1022)	Wafer Phillips Recess

Product Code SKU	Gauge		Length	Threads Per inch (TPI)	Thread Length	Diameter (Max)	Head Diameter (Max)	Drive Phillips	Drilling Point Length
	#	(mm)	L (mm)		(mm)	D (mm)	A (mm)	#	C (mm)
SDWY08-1812	8	4.2	12	18	Full	4.09-4.21	7.7-8.2	2	4.7-5.7
Coarse Thread									
SDWY10-1616	10	4.8	16	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWY10-1622	10	4.8	22	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWY10-1630	10	4.8	30	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWY10-1640	10	4.8	40	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
SDWY10-1650	10	4.8	50	16	Full	4.62 – 4.82	9.0-9.5	2	5.7-6.7
Fine Thread									
SDWY10-2416	10	4.8	16	24	Full	4.66 – 4.83	9.0-9.5	2	5.7-6.7
SDWY10-2422	10	4.8	22	24	Full	4.66 – 4.83	9.0-9.5	2	5.7-6.7
SDWY10-2430	10	4.8	30	24	Full	4.66 – 4.83	9.0-9.5	2	5.7-6.7
SDWY10-2440	10	4.8	40	24	Full	4.66 – 4.83	9.0-9.5	2	5.7-6.7

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

