




Open Blind Rivet

Blind Rivets are now capable in every industrial field to replace Welding, Tapping Screws or Bolts & Nuts and to fasten materials speedy and securely from one side of the work by using an exclusive fastening tool.







Advantage:

* Optimum clamp-up force

- * Accommodates oversized and irregular sized holes applications
- * High mandrel head retention
- * Vibration and moisture resistant
- * Reduced inventory, it can replace open type up to the size

Applications

- **Plastics** Automotive
- Furniture industry

| | Material | Finish | Head |
|----------|----------|-------------|--------------|
| Body: | Steel | Zinc Plated | Dome (Truss) |
| Mandrel: | Steel | Zinc Plated | Multi-Grip |

| Product Code SKU | Size | | Body Length | Head Height | Head Dia. (Max) | Mandrel (Ref) | Hole Size | Grip Range | Tensile | Shear |
|---------------------|--------|-------|----------------|----------------|--------------------|------------------|-----------|------------|---------|-------|
| | D (mm) | Inch | L (±1)mm | E (mm) | H (mm) | P (mm) | (mm) | (mm) | N | N |
| SSDMG4-3 | 3.2 | 1/8" | 8 | 1.3 | 6.7 | 27 | 3.3-3.4 | 1.0-4.0 | 1200 | 1000 |
| SSDMG4-5 | 3.2 | 1/8" | 12 | 1.3 | 6.7 | 27 | 3.3-3.4 | 1.5-8.0 | 1200 | 1000 |
| | | | | | | | | | | |
| SSDMG5-3 | 4.0 | 5/32" | 10 | 1.7 | 8.4 | 27 | 4.1-4.2 | 1.5-5.0 | 2000 | 1500 |
| SSDMG5-5 | 4.0 | 5/32" | 14 | 1.7 | 8.4 | 27 | 4.1-4.2 | 1.5-9.0 | 2000 | 1500 |
| | | | | | | | | | | |
| SSDMG6-4 | 4.8 | 3/16" | 12 | 2.0 | 10.1 | 27 | 4.9-5.0 | 2.0-6.5 | 2900 | 2400 |
| SSDMG6-6 | 4.8 | 3/16" | 16 | 2.0 | 10.1 | 27 | 4.9-5.0 | 3.0-10.5 | 2900 | 2400 |
| SSDMG6-8 | 4.8 | 3/16" | 18 | 2.0 | 10.1 | 27 | 4.9-5.0 | 5.0-12.5 | 2900 | 2400 |
| SSDMG6-10 | 4.8 | 3/16" | 20 | 2.0 | 10.1 | 27 | 4.9-5.0 | 7.0-14.5 | 2900 | 2400 |
| SSDMG6-12 | 4.8 | 3/16" | 25 | 2.0 | 10.1 | 27 | 4.9-5.0 | 11.0-19.0 | 2900 | 2400 |

1300 532 803 sales@tower-tr.com.au www.tower-tr.com.au

