


## Stitch Screws - Needle Point

Stitch Screws are used for fixing fixtures into metals or wooden objects, while also retaining the ability to attach metals together.



Features	Applications	Installation Speed	Drill Capacity
Button head has a large head profile that gives more surface coverage when fastened  Needle Point	<ul style="list-style-type: none"> <li>Timber</li> <li>Plasterboard</li> <li>Thin Sheet Steel</li> </ul>	2500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated	Carbon Steel	Button Phillips Recess

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length (mm)	Diameter (Max) D(mm)	Head Diameter (Max) A(mm)	Head Height (Max) H(mm)	Drive Phillips #
	#	(mm)							
STBG0812	8	4.2	12	15	Full	4.11 – 4.26	11.20	2.1	2
STBG0815	8	4.2	15	15	Full	4.11 – 4.26	11.20	2.1	2
STBG0820	8	4.2	20	15	Full	4.11 – 4.26	11.20	2.1	2
STBG0825	8	4.2	25	15	Full	4.11 – 4.26	11.20	2.1	2
STBG0830	8	4.2	30	15	Full	4.11 – 4.26	11.20	2.1	2

## Class 3 Screws

- Suitable for external use in mild urban, moderate industrial or moderate marine environments.
- Moderate industrial environments refer to atmosphere with medium pollution from industry.
- Moderate marine environments refer to coastal areas with low airborne salinity.
- Corrosivity as classified in accordance with AS 3566.2-2002,5.3 and ISO 9223.

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

