





Stitch Screws - Needle Point

Stitch Screws are used for fixing fixtures into metals or wooden objects, while also retaining the ability to attach metals together.



Features	Applications	Installation Speed	Drill Capacity
Flat top has a low profile head Needle Point	<ul style="list-style-type: none"> Timber Plasterboard Thin Sheet Steel 	2500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert [®] Plated Zinc Plated	Carbon Steel	Hex Flange Washer

Product Code SKU	Gauge		Length	Threads per inch (TPI)	Thread Length	Diameter (Max)	Head Diameter (Max)	Head Height H (Max)	Hex. Socket
	#	(mm)	L (mm)		(mm)	D(mm)	A(mm)	H(mm)	(inch)
Ruspert[®]Plated									
STHG0815	8	4.2	15	15	Full	4.09 - 4.21	9.40 - 10.29	3.71 - 4.29	1/4"
STHG1020	10	4.8	20	12	Full	4.78 - 4.93	10.85 - 11.45	4.70 - 5.10	5/16"
Serration Under head									
STHGS0815	8	4.2	15	15	Full	4.09 - 4.21	9.40 - 10.29	3.71 - 4.29	1/4"
With NEO									
STHGN0815	8	4.2	15	15	Full	4.09 - 4.21	9.40 - 10.29	3.71 - 4.29	1/4"
STHGN1020	10	4.8	20	12	Full	4.78 - 4.93	10.85 - 11.45	4.70 - 5.10	5/16"
Zinc Plated									
STHZ0812	8	4.2	12	15	Full	4.09 - 4.21	9.40 - 10.29	3.71 - 4.29	1/4"
STHZ0815	8	4.2	15	15	Full	4.09 - 4.21	9.40 - 10.29	3.71 - 4.29	1/4"

Ruspert[®]Plated – Class3 - Corrosivity as classified in accordance with AS 3566-2002, 5.3 and ISO 9223.

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

