



## Type 17 Screws

### AS3566 Class 4

Suitable for external use in heavy industrial or severe marine environments. Heavy industrial environments refer to atmosphere with medium pollution from industry. Severe marine environments refer to coastal areas with high airborne salinity. Severe marine environments refer to coastal areas with high airborne salinity. Corrosively as classified in accordance with AS 3566-2002, 5.4 and ISO 9223.



Features	Applications	Installation Speed	Drill Capacity
Type 17 screws are a thread cutting screw for wood. Designed with a coarse tapping screw thread and a sharp point for capturing wood chips.	<ul style="list-style-type: none"> <li>Fix timber to timber</li> <li>Fix thin steel to timber</li> <li>Substrates where a flush finish is required</li> </ul>	1500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated	Carbon Steel	Countersunk Phillips Recess

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length TL(mm)	Diameter (Max) D(mm)	Head Diameter (Max) A(mm)	Phillips Drive #	Cutting Length (mm)
	#	(mm)							
T17CC1030	10	4.8	30	12	Full	4.78 – 4.93	8.64-9.77	2	8.0–12.0
T17CC1040	10	4.8	40	12	Full	4.78 – 4.93	8.64-9.77	2	8.0–12.0
T17CC1050	10	4.8	50	12	Full	4.78 – 4.93	8.64-9.77	2	8.0–12.0
T17CC1075	10	4.8	75	12	Full	4.78 – 4.93	8.64-9.77	2	8.0–12.0

1300 532 803  
[sales@tower-tr.com.au](mailto:sales@tower-tr.com.au)  
[www.tower-tr.com.au](http://www.tower-tr.com.au)

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

