



### T17HCN–AS3566 Class 4

Suitable for external use in heavy industrial or severe marine environments. Heavy industrial environments refer to atmosphere with medium pollution from industry. Severe marine environments refer to coastal areas with high airborne salinity. Severe marine environments refer to coastal areas with high airborne salinity. Corrosively as classified in accordance with AS 3566-2002, 5.4 and ISO 9223.



Features	Applications	Installation Speed	Drill Capacity
Type 17 screws are a thread cutting screw for wood. Designed with a coarse tapping screw thread and a sharp point for capturing wood chips.	<ul style="list-style-type: none"> <li>Fix timber to timber</li> <li>Cladding to timber</li> <li>Roofing &amp; Cladding to timber</li> </ul>	1500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert <sup>®</sup> Plated	Carbon Steel	Hex Flange Washer With EPDM NEO Washer

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length (mm)	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Head Height H (mm)	Hex. Socket (inch)	Cutting Length S (mm)
	#	(mm)								
T17HCN1425	14	6.3	25	10	Full	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN1440	14	6.3	40	10	Full	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN1450	14	6.3	50	10	Full	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN1465	14	6.3	65	10	50	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN1475	14	6.3	75	10	50	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN1490	14	6.3	90	10	75	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14100	14	6.3	100	10	75	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14115	14	6.3	115	10	100	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14125	14	6.3	125	10	100	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14150	14	6.3	150	10	100	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14175	14	6.3	170	10	100	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HCN14200	14	6.3	200	10	100	6.3 – 6.45	14.0 - 14.7	6.35 - 7.0	3/8"	8.0 – 12.0

1300 532 803  
sales@tower-tr.com.au  
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

