


Type 17 Screws

Zinc Yellow



Features	Applications	Installation Speed	Drill Capacity
Type 17 screws are a thread cutting screw for wood. Designed with a coarse tapping screw thread and a sharp point for capturing wood chips.	<ul style="list-style-type: none"> Fix timber to timber Cladding to timber 	1500 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Yellow Zinc Plated	Carbon Steel	Hex Flange Washer

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length (mm)	Diameter (Max) D (mm)	Head Diameter (Max) A (mm)	Head Height H (mm)	Hex. Socket (inch)	Cutting Length S (mm)
	#	(mm)								
T17HY1020	10	4.8	20	12	Full	4.78 – 4.93	10.85 – 11.45	4.7 – 5.1	5/16"	8.0 – 12.0
T17HY1025	10	4.8	25	12	Full	4.78 – 4.93	10.85 – 11.45	4.7 – 5.1	5/16"	8.0 – 12.0
T17HY1220	12	5.5	20	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1225	12	5.5	25	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1235	12	5.5	35	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1240	12	5.5	40	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1245	12	5.5	45	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1250	12	5.5	50	11	Full	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1265	12	5.5	65	11	50	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1275	12	5.5	75	11	50	5.46 – 5.74	14.0 – 14.2	5.08 - 6.14	5/16"	8.0 – 12.0
T17HY1425	14	6.3	25	10	Full	6.3 - 6.45	14.0 – 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HY1450	14	6.3	50	10	40	6.3 - 6.45	14.0 – 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HY1465	14	6.3	65	10	50	6.3 - 6.45	14.0 – 14.7	6.35 - 7.0	3/8"	8.0 – 12.0
T17HY1475	14	6.3	75	10	50	6.3 - 6.45	14.0 – 14.7	6.35 - 7.0	3/8"	8.0 – 12.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

