



Type 17 Screws



Features	Applications	Installation Speed	Drill Capacity
Type 17 screws are a thread cutting screw for wood. Designed with a coarse tapping screw thread and a sharp point for capturing wood chips.	<ul style="list-style-type: none"> Fix timber to timber Decking Substrates where a flush finish is required 	1800 RPM max drill speed	<1.0mm thin steel

Finish	Material	Head
Ruspert [®] Plated Zinc Yellow Plated	Carbon Steel	Countersunk rib. Square Recess

Product Code SKU	Gauge		Length (mm)	Threads per inch (TPI)	Thread Length TL(mm)	Diameter (Max) D(mm)	Head Diameter (Max) A(mm)	Square Drive #	Cutting Length (mm)
	#	(mm)							
AS3566 Class4									
T17SQC1250	12	5.5	50	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQC1265	12	5.5	65	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQC1275	12	5.5	75	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQC12100	12	5.5	100	11	75	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQC12125	12	5.5	125	11	100	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
Zinc Yellow									
T17SQY1250	12	5.5	50	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQY1265	12	5.5	65	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQY1275	12	5.5	75	11	Full	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQY12100	12	5.5	100	11	75	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0
T17SQY12125	12	5.5	125	11	100	5.46 - 5.74	9.88-11.12	3	10.0 – 12.0

1300 532 803
sales@tower-tr.com.au
www.tower-tr.com.au

Disclaimer: every effort has been made to ensure the information provided in this document is accurate and up to date. However, Tower Fastening System does not guarantee or warrant the accuracy, completeness, or currency of the information provided.

